

## Model Description GLYCERINE FILLED PRESSURE GAUGES

High & Low Pressure Gauges  
Suitable For Installation On Refrigerant Plants or Equipment  
With Pulsating Pressure and Mechanical Vibration  
Readings in BAR/PSI for R22, R134a & R404a refrigerants

**ESG-G15H4** Dimensions : Ø 63mm  
Mount Type : Panel Mount  
Range : -1 ... +15 BAR/PSI (Low)  
Accuracy : Class 1.6  
Case : ANSI 304 Stainless Steel  
Window : Plexiglas  
Ring : ANSI 304 Stainless Steel, Polished  
Conn. Size : 1/4" SAE Back Connection (Brass)  
Protection : IP65 according IEC29



**ESG-G15H4**

**ESG-G35H4** Dimensions : Ø 63mm  
Mount Type : Panel Mount  
Range : -1... +35 BAR/PSI (High)  
Accuracy : Class 1.6  
Case : ANSI 304 Stainless Steel  
Window : Plexiglas  
Ring : ANSI 304 Stainless Steel, Polished  
Conn. Size : 1/4" SAE Back Connection (Brass)  
Protection : IP65 according IEC29



**ESG-G35H4**

**ESG-G15U4** Dimensions : Ø 63mm  
Mount Type : Panel Mount  
Range : -1 ... +15 BAR/PSI (Low)  
Accuracy : Class 1.6  
Case : ANSI 304 Stainless Steel  
Window : Plexiglas  
Ring : ANSI 304 Stainless Steel, Polished  
Conn. Size : 1/4" SAE Bottom Connection (Brass)  
Protection : IP65 according IEC29



**ESG-G15U4**

**ESG-G35U4** Dimensions : Ø 63mm  
Mount Type : Panel Mount  
Range : -1... +35 BAR/PSI (High)  
Accuracy : Class 1.6  
Case : ANSI 304 Stainless Steel  
Window : Plexiglas  
Ring : ANSI 304 Stainless Steel, Polished  
Conn. Size : 1/4" SAE Bottom Connection (Brass)  
Protection : IP65 according IEC29



**ESG-G35U4**